



PROGLO

EXTRA-HIGH GLOSS MARBLE POLISHING POWDER

DESCRIPTION

PROGLO is designed to restore the extra high gloss of Marble and Terrazzo flooring using semi-wet system at the shortest time. The high area coverage of PROGLO gives value for money, it covers approximately 60 sqm using 1Kg of PROGLO.

APPLICATION

PROGLO rejuvenates dull marble flooring using a single disc floor scrubber weighing 50Kg and above and running at 160-170RPM with a Red/White 400mm Pad soak the 3M red/white pad entirely into water, spread ½ cup PROGLO on dull marble flooring, if dull marble flooring has lots of existing scratch marks, it is advisable to use CF Carbon Pad with water and scrub before application of PROGLO for restoration.

FEATURES

- **No scratch and scuff marks cause by waxing**
- **No ring marks cause by steel wool**
- **Non-yellowish cause by waxing**
- **Super-fast High Shine**
- **High productivity**
- **Wet look**
- **No staining on white Marble**

METHOD OF USE

- Spread PROGLO powder on dull marble flooring.
- Soak 3M red/white pad into a pail of water and place on top of the spread PROGLO powder.
- Operate single disc scrubber from left to right in slow movement 2 – 3 times over one to two slabs of Marble tile.
- Use rubber squeeze to push slurry from the done surfaces to ascertain high gloss and continue process.
- Add water to PROGLO slurry to ensure wetness during operation to prevent the slurry from hardening on the pad.
- Repeat process until Proglo slurry turns greyish. (this shows that the slurry has reach its fullest potential)
- Rinse floor with clean water and use Wet & Dry Vacuum to suck up.
- Dry marble flooring by buffing with clean & new 3M white pad.

PACKING

1Kg tub.

Important Notes

Chemforce product data sheets are regularly reviewed and available on request. The successful use of this product is dependent on a number of factors. As the information contained in this literature can only be of a general nature, it is advisable to consult our technical department if there is any doubt about the correct use of this product in a particular application. Our Sales and Technical representatives are available to provide further technical and commercial assistance.

CHEMFORCE PTE LTD

2B Sungei Kadut Drive,
Singapore 729555.

Tel: +65 6365 2833 Fax: +65 6365 2700

Email: chemforc@singnet.com.sg

Website: www.chemforce.com.sg